



2025 ÜRÜN KATALOĞU

Endüstriyel ve
Otomotiv Yağları

www.cooloil.com.tr

ENDÜSTRİYEL VE
OTOMOTİV YAĞLARINDA

YENİ NESİL ÇÖZÜMLER



”

**Bizim için önemli olan
sadece yağ satmak
değil, aynı zamanda
işletmenize değer
katmaktır.**

Cool Oil olarak her ürünümüzde kaliteyi, güveni ve sürdürülebilirliği ön planda tutuyoruz.

ASLI YILDIRIM

CEO

Yıllardır edindiğimiz tecrübeyi, yenilikçi teknolojiler ve güçlü Ar-Ge çalışmalarımızla birleştiriyoruz. Hedefimiz sadece yüksek performanslı yağlar üretmek değil, aynı zamanda çevreye duyarlı, sürdürülebilir çözümler sunmaktır. Siz değerli iş ortaklarımızla birlikte geleceğe güvenle ilerliyoruz.

ENDÜSTRİYEL YAĞLAR SERİSİ



Cool Oil HD-46 16 Litre Motor Yağı

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



Cool Oil 10W/30 KLFD422 Motor Yağı

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



Dişli ve Şanzıman Yağı – Gear Oil

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



ENDÜSTRİYEL YAĞLAR SERİSİ



Cool Oil 20W50 – 16 Litre Motor Yağı

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



Cool Oil HD-68 16 Litre Yüksek Performanslı Hidrolik Yağ

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



Cool Oil SAE 10 16 Litre Motor Yağı

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



ENDÜSTRİYEL YAĞLAR SERİSİ



Cool Oil SAE 15W40 16 Litre Motor Yağı

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



Cool Oil SAE 30 16 Litre Motor Yağı

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



Cool Oil Kızak Yağ 18 Litre

- Density at 15°C (ASTM D4052): 0.880 g/ml
- Kinematic Viscosity at 40°C (ASTM D445): 41.4 – 50.6 mm²/s
- Kinematic Viscosity at 100°C (ASTM D445): 7 mm²/s
- Viscosity Index (ASTM D2270): 107
- Pour Point (ASTM D6892): -20 °C
- Flash Point COC (ASTM D92): 220 °C



Daha Fazla Bilgi ve İş Birliği İçin

Cool Oil, yüksek performanslı madeni yağ çözümleri ve sürdürülebilir üretim anlayışıyla iş ortaklarının yanında olmaya devam ediyor. Ürünlerimiz, ihracat faaliyetlerimiz ve distribütörlük fırsatları hakkında daha fazla bilgi almak için bizimle iletişime geçin.



Müşteri Hizmetleri

0850 302 50 06

Cool Oil Madeni Yağ Geri Dönüşüm Ltd. Şti.

E-Posta :

info@cooloil.com.tr

Adres :

Güldiken OSB Mah. Aşıkpaşa Cad.
No:3, Merkez / Kırşehir – TÜRKİYE



*QR Kodunu Tara,
E-Mağazamıza Ulaş!*